

SUPPLEMENTAL SPECIFICATION

AMENDMENT TO SECTION 411 – PLANT MIX SURFACE TREATMENT

The purpose of this Supplemental Specification is to:

- *Require the use of pneumatic tired rollers on all paving done under Section 411 (06/06/17)*
 - *Remove Pay Items 411.15 & 411.19 (04/01/18)*
- *Ensure Tack used for PMST and leveling course is a Pay Item (07/06/18)*
- *Remove Pay Item 411.43; revise Pay Item 411.3 description, revise 2.1.2 and 3.4.7 remove AC reference; and delete reference to 3/4" PMST (2.1.2) (01/11/24)*

Amend 2.1.2 to read:

2.1.2 Unless a volumetric mix design has been performed by the Contractor, the composition of the mixtures shall conform to historical gradation and binder content. Leveling Course, Plant Mix Surface Treatment (PMST) Paver Shim, and PMST Paver Spot Drag Shim shall be Type H unless otherwise noted.

Amend 3.4.7 to read:

3.4.7 When Paver Shim is specified, in areas of extreme deformation of the existing roadway, some amount of dragging is expected in placing this wearing course.

Add to 3.5.5:

3.5.5 Intermediate rolling shall be done by a pneumatic-tired roller.

Amend 5.1.1 to read:

5.1.1 Tack coat material required under 3.4.2 for the leveling course and plant mix surface treatment items will be paid for as specified in 410.5.2.

Replace Pay Items and units with the following:

Pay items and units:

411.1	Hot Bituminous Concrete Leveling Course	Ton
411.3	Plant Mix Surface Treatment, Paver Shim	Ton
411.51	Plant Mix Surface Treatment, Paver Spot Drag Shim	Ton